





PRODUCT MATERIAL	Die-cast aluminium
LIGHT SOURCE	Bridgelux DtW
MODULE LIFETIME	Approx. 50.000 hours
DRIVER	Including phase cut dimmable driver
COLORS (Δ)	○ 3 = RAL 9003 white ● 5 = RAL 9005 black
BEAM ANGLE	24°
ADJUSTABLE	Rotating 350°, 55° tiltable
DIMMABLE	Yes
SIZE	Ø59 X 62mm



OPTIONS

OPTIONAL BEAM ANGLE	36° Art. no.: 3066.010.36.0
	50° Art. no.: 3066.010.50.0
ANTI-GLARE RING	Black Included
	Gold Art. no.: 3066.030.00.9
HONEYCOMB	Art. no.: 3066.040.00.0
DRIVER OPTIONS	1/10V 250mA 1-14W Art. no.: 0114.250.30.0 Size: 111 x 52 x 22mm
	DALI 250mA 6-13W Art. no.: 0114.250.40.1 Size: 97,2 x 43 x 30mm
POWER CABLE OPTIONS Connected to driver/fixture	Europlug 2000mm 2 X 0,75 Art. no.: 0502.075.20.0
	Wieland GST18/3 male 2000mm 3 X 0,75 Art. no.: 0501.183.20.0
	Wieland T connector GST18/3 200mm 3 X 0,75 Art. no.: 0500.183.20.0


Design Patent Certificate
No: ZL 2019 3 0427879.1 Recessed Mount Venus Patent



INFORMATION

Full warranty only applies when fixture is purchased in combination with recommended driver.

ANTI-GLARE RING



HONEYCOMB



ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	mA
4066.125.24.Δ	DtW	Bridgelux	900lm	10W	90lm/W	1800-3000K >90	>90	50.000 Hrs	250mA

Δ See colors

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.